



# 90 Degree Cat.6 E-Style Keystone Jack Model: 1305-04017




#### **Features:**

- --- All-in-one Punch down and wire trim process
- → Multi use E -Jacks (Keystones), can be used in
- E-Tool and also standard punch down tool
- → E-Tool can be used for either Cat6 Keystone E-Jacks
- --- Jacks can be inserted either side of E-Tool

















### **Mechanical:**

- → Plug insertion life:750 cycle min.
- → Plug retention force:30 lbs min.

#### **Electrical:**

- → Current rating:1.5 Amps
- <sup>→</sup> Insulation resistance:500Mega-ohms min.
- → Contact resistance:20 milli -ohms max.
- → DC resistance:0.1 ohms max.
- → Transmission quality verified up to 100MHz

## **Physical:**

- $\stackrel{\dots}{\longrightarrow}$  Multi use E -Jack can be used in E-Tool and also punch down tool
- → 110 and krone dual type IDC termination
- → IDC connector accepts 22 -24 AWG solid wire
- ightharpoonup Jack wiring:50 u" gold pla ightharpoonup ted over 100u" nickel
- → Housing: High impact flame retardant plastic UL94V -0 rated
- → Operating temperatures : 20 to 60°C

## **Industry Standard:**

- → UL Listed
- → Meet all requirements specified in connecting hardware requirement of ANSI/TIA 568-C.2 Cat.6

