

Tackle your everyday office tasks with an affordable, full-featured MFP. Easily Print, Copy, Scan and Fax from one compact machine—with Ethernet connectivity and energy-saving features.

Print: Up to 19 ppm black (letter); Up to 18 ppm black (A4); First page out black:

As fast as 8.5 sec

Scan: Up to 1200 x 1200 dpi; Scan Type: Flatbed, ADF

Copy: Up to 600 x 400 dpi resolution; Up to 99 copies maximum number of copies

Fax: 33.6 kbps; Letter: 3 sec per page

Paper Handling: 150-sheet input tray, 100-sheet face-down bin

Standard Connectivity: Hi-Speed USB 2.0 port, 10/100Base-T Ethernet network port,

RJ-11 Telephone port

Monthly Volume (Duty Cycle): Up to 8,000 pages







Get more done—affordably—with a full-featured MFP

- Share a printing network, using built-in Ethernet, and save office space with the compact size.
- Print high-quality documents with bold text and sharp images, using Original HP print cartridges.
- Send and receive faxes from your PC, using the 33.6 kbps fax.
- Print documents at up to 19 ppm letter/18 ppm A4. Start printing fast with Instant-on Technology.

Get up and running quickly and easily

- Install in a flash on your PC or Netbook—without a CD—using HP Smart Install.¹
- Set up and start printing fast with an easy-to-use control panel. Copy a duplex ID onto one page with ID Copy.
- Connect the MFP directly to a PC or Netbook via the included Hi-Speed USB 2.0 port
- Ensure reliable printing with an HP all-in-one print cartridge. Easily replace it with HP SureSupply.²

Reduce your impact and protect your bottom line

- Conserve energy with HP Auto-On/Auto-Off Technology³, Instant-on Technology and Instant-on Copy.
- Reduce your impact—pre-installed cartridges decrease packaging. Recycle easily with HP Planet Partners.⁴
- Get the services, solutions, software and support of HP Total Care.
- Save energy with an ENERGY STAR® qualified MFP.

ecohighlights

HP LASERJET PRO M1212NF MULTIFUNCTION PRINTER

- Save energy—HP Auto-On/Auto-Off Technology turns your printer on when you need it, off when you don't.¹
- Save up to four times the energy with Instant-on Copy.²

ENERGY STAR® Qualified Product

¹HP Auto-On and Auto-Off capabilities subject to printer and settings.

²When compared with fluorescent tubes, Instant-on Copy with LED technology drops energy use by 4 times in idle mode and 1.4 times in copy mode.

www.hp.com/ecosolution

Please recycle your computing hardware and printing supplies Find out how at our website. (4)

¹HP Smart Install works with Windows only. ²Program features and availability may vary by country. For more information, visit http://www.hp.com/learn/suresupply. ³HP Auto-On and Auto-Off capabilities subject to printer and settings. ⁴HP toner cartridge return and recycling is available in 49 countries and territories around the world, covering 88% of the addressable market; see http://www.hp.com/recycle for details.













				TIO	

TECHNICAL SPECIFICA	IIONS
FUNCTIONS	Print, copy, scan, fax
STANDARD PRINTER LANGUAGES	Host-based
PRINT RESOLUTION	Black (Best): Up to 600 x 600 dpi (1200 dpi effective); Black (Normal): Up to 600 x 400 dpi
PRINT TECHNOLOGY RESOLUTION	FastRes 600; FastRes 1200
PRINT TECHNOLOGY	Laser
PRINT SPEED ¹	Black (Letter): Up to 19 ppm; Black (A4): Up to 18 ppm; First Page Out Black ² : As fast as 8.5 sec
NUMBER OF PRINT CARTRIDGES	1 (black)
PRINTER SMART SOFTWARE FEATURES	Smart Install, Simplified control panel, Auto-On/Auto-Off, Compact design
RECOMMENDED MONTHLY PAGE VOLUME	250 to 2,000
DUTY CYCLE (MONTHLY)	Up to 8,000 pages
TWAIN VERSION	Version 1.9
COLOR SCANNING	Yes
SCAN TYPE	Flatbed, ADF
SCAN RESOLUTION	Enhanced: Up to 19,200 dpi; Hardware: Up to 1200 x 1200 dpi;
	Optical: Up to 1200 dpi
SCAN SPEED	4 x 6 in (10 x 15 cm) color photo to file: less than 7 sec for single; Black (Normal): Up to 6 ppm; Color (Normal): Up to 3 ppm; ADF: Up to 7.4 ppm (black and white), Up to 3 ppm (color)
GRAYSCALE LEVELS/BIT DEPTH	256/24-bit
SCAN FILE FORMAT	JPEG, TIF (compressed and uncompressed), PDF, GIF, BMP
SCAN INPUT MODES	Scanning via HP LaserJet scan application or TWAIN—or WIA-compliant application software
SCAN SIZE MAXIMUM	ADF: 8.5 x 14 in (216 x 356 mm); Flatbed: 8.5 x 11.7 in (216 x 297 mm)
COPY RESOLUTION	Black (Text and Graphics): Up to 600 x 400 dpi; Color (Text and Graphics): Up to 600 x 400 dpi
COPY SPEED	Black (Letter): Up to 19 cpm; Black (A4): Up to 18 cpm
MAXIMUM NUMBER OF COPIES	Up to 99 copies
COPIER RESIZE	25 to 400%
FAX RESOLUTION	Black and White, Best Mode: Up to 300 x 300 dpi; Black and White, Standard Mode: 203 x 98 dpi
FAX SPEED	33.6 kbps; Letter: 3 sec per page
FAX FEATURES	Fax Memory (Letter): Up to 500 pages; Auto Fax Reduction Supported: Yes; Auto-Redialing: Yes; Fax Delayed Sending: Yes; Distinctive Ring Detection Supported: Yes; Fax Forwarding Supported: Yes; Fax Fohne TAM Interface Supported: Yes; Fax Polling Supported: Yes; Fax Telephone Mode Supported: Yes; Junk Barrier Supported: Yes; Maximum Speed Dialing Numbers: Up to 100 numbers; PC Interface Supported: Yes; Remote Retrieval Capability Supported: Yes;
MODEM	Telephone Handset Supported: No
	Telephone Handset Supported: No 33.6 kbps
STANDARD CONNECTIVITY	33.6 kbps
STANDARD CONNECTIVITY NETWORK CAPABILITIES	33.6 kbps
	33.6 kbps Hi-Speed USB 2.0 port, 10/100Base-T Ethernet network port, RJ-11 Telephone port Via built-in 10/100Base-T TCP/IP networking;
NETWORK CAPABILITIES	33.6 kbps Hi-Speed USB 2.0 port, 10/100Base-T Ethernet network port, RJ-11 Telephone port Via built-in 10/100Base-T TCP/IP networking; Network Ready: Standard (built-in Ethernet) 2-line, 16-character display, menu and navigation buttons (Setup/Enter, Left, Right, Cancel), copy control buttons (Number buttons, Lighter/Darker, More copy settings, Start Copy), Fax control buttons (Redial, Start Fax), 3 LED indicator lights (Attention,
NETWORK CAPABILITIES CONTROL PANEL	33.6 kbps Hi-Speed USB 2.0 port, 10/100Base-T Ethernet network port, RJ-11 Telephone port Via built-in 10/100Base-T TCP/IP networking; Network Ready: Standard (built-in Ethernet) 2-line, 16-character display, menu and navigation buttons (Setup/Enter, Left, Right, Cancel), copy control buttons (Number buttons, Lighter/Darker, More copy settings, Start Copy), Fax control buttons (Redial, Start Fax), 3 LED indicator lights (Attention, Ready, Toner low)
NETWORK CAPABILITIES CONTROL PANEL OUTPUT FILE FORMAT DIGITAL SENDING	33.6 kbps Hi-Speed USB 2.0 port, 10/100Base-T Ethernet network port, RJ-11 Telephone port Via built-in 10/100Base-T TCP/IP networking; Network Ready: Standard (built-in Ethernet) 2-line, 16-character display, menu and navigation buttons (Setup/Enter, Left, Right, Cancel), copy control buttons (Number buttons, Lighter/Darker, More copy settings, Start Copy), Fax control buttons (Redial, Start Fax), 3 LED indicator lights (Attention, Ready, Toner low) PDF, TIF, BMP, GIF, JPG
NETWORK CAPABILITIES CONTROL PANEL OUTPUT FILE FORMAT DIGITAL SENDING STANDARD FEATURES	33.6 kbps Hi-Speed USB 2.0 port, 10/100Base-T Ethernet network port, RJ-11 Telephone port Via built-in 10/100Base-T TCP/IP networking; Network Ready: Standard (built-in Ethernet) 2-line, 16-character display, menu and navigation buttons (Setup/Enter, Left, Right, Cancel), copy control buttons (Number buttons, Lighter/Darker, More copy settings, Start Copy), Fax control buttons (Redial, Start Fax), 3 LED indicator lights (Attention, Ready, Toner low) PDF, TIF, BMP, GIF, JPG Scan to E-mail, scan to application, scan to file
NETWORK CAPABILITIES CONTROL PANEL OUTPUT FILE FORMAT DIGITAL SENDING STANDARD FEATURES DISPLAY MAXIMUM/STANDARD	33.6 kbps Hi-Speed USB 2.0 port, 10/100Base-T Ethernet network port, RJ-11 Telephone port Via built-in 10/100Base-T TCP/IP networking; Network Ready: Standard (built-in Ethernet) 2-line, 16-character display, menu and navigation buttons (Setup/Enter, Left, Right, Cancel), copy control buttons (Number buttons, Lighter/Darker, More copy settings, Start Copy), Fax control buttons (Redial, Start Fax), 3 LED indicator lights (Attention, Ready, Toner low) PDF, TIF, BMP, GIF, JPG Scan to E-mail, scan to application, scan to file 2-line LCD
NETWORK CAPABILITIES CONTROL PANEL OUTPUT FILE FORMAT DIGITAL SENDING STANDARD FEATURES DISPLAY MAXIMUM/STANDARD MEMORY	33.6 kbps Hi-Speed USB 2.0 port, 10/100Base-T Ethernet network port, RJ-11 Telephone port Via built-in 10/100Base-T TCP/IP networking; Network Ready: Standard (built-in Ethernet) 2-line, 16-character display, menu and navigation buttons (Setup/Enter, Left, Right, Cancel), copy control buttons (Number buttons, Lighter/Darker, More copy settings, Start Copy), Fax control buttons (Redial, Start Fax), 3 LED indicator lights (Attention, Ready, Toner low) PDF, TIF, BMP, GIF, JPG Scan to E-mail, scan to application, scan to file 2-line LCD
NETWORK CAPABILITIES CONTROL PANEL OUTPUT FILE FORMAT DIGITAL SENDING STANDARD FEATURES DISPLAY MAXIMUM/STANDARD MEMORY PROCESSOR TYPE/SPEED	33.6 kbps Hi-Speed USB 2.0 port, 10/100Base-T Ethernet network port, RJ-11 Telephone port Via built-in 10/100Base-T TCP/IP networking; Network Ready: Standard (built-in Ethernet) 2-line, 16-character display, menu and navigation buttons (Setup/Enter, Left, Right, Cancel), copy control buttons (Number buttons, Lighter/Darker, More copy settings, Start Copy), Fax control buttons (Redial, Start Fax), 3 LED indicator lights (Attention, Ready, Toner low) PDF, TIF, BMP, GIF, JPG Scan to E-mail, scan to application, scan to file 2-line LCD 64 MB Marvell processor/400 MHz

MEDIA WEIGHT	ADF : 60 to 90 g/m² (16 to 24 lb) bond; Tray 1: 16 to 43 lb
CUSTOM MEDIA SIZES	3 x 5 to 8.5 x 14 in (76 x 127 to 216 x 356 mm)
AUTO DOCUMENT FEEDER CAPACITY	Standard, 35 sheets
PRINT HANDLING	150-sheet input tray, 100-sheet face-down bin Input Capacity: Up to 150 sheets, Up to 10 envelopes; Output Capacity: Up to 100 sheets, Up to 10 envelopes, Up to 75 sheets transparencies
POWER	Power Supply Type: Built-in power supply; Power Requirements: Input voltage 110 to 127 VAC (+/- 10%), 60 Hz (+/- 2 Hz); 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); Power Consumption: 375 watts active, 0.3 watts off, 2 watts powersave, 4.7 watts standby; Typical Electricity Consumption (TEC) Number: 0.771 kWh/Week;
	ENERGY STAR® qualified models; see http://www.hp.com/go/energystar
SOFTWARE INCLUDED	Host-based print drivers, TWAIN, WIA, Scan to application, XPS driver, Mac driver, Send Fax, Toolbox
COMPATIBLE OPERATING SYSTEMS	Microsoff® Windows® 7, Windows Vista®, Windows® XP, Windows® Server 2003; Mac OS X v 10.4, v 10.5, v 10.6; Linux (see: http://www.hplip.net)
MINIMUM SYSTEM REQUIREMENTS	PC: Microsoft® Windows® 7, Windows Vista®, Windows® XP, Windows® Server 2003, Windows® Server 2008: 1 GHz processor, 1 GB RAM, 700 MB free hard disk space, SVGA 800 x 600 with 16-bit color display, Internet Explorer 5.5 or higher, USB or Ethernet port Mac: Mac OS X v 10.4, v 10.5, v 10.6; PowerPC G3, G4, G5, or Intel processors; 1 GB RAM; 200 MB available hard disk space; CD-ROM drive; USB or network port
ACOUSTIC ²	Acoustic Power Emissions: 6.3 B(A); Acoustic Power Emissions (Ready): Inaudible; Acoustic Pressure Emissions: 50 dB(A)
	I to the second of the second
OPERATING ENVIRONMENT	Operating Temperature Range: 10 to 32.5° C; Recommended Operating Temperature: 50 to 91° F (10 to 32.5° C); Maximum Operating Temperature: 50 to 91° F; Storage Temperature Range: 32 to 95° F (0 to 35° C); Non-Operating Humidity Range: 10 to 80% RH; Operating Humidity Range: 10 to 80% RH; Recommended Humidity Operating Range: 10 to 80% RH
	Operating Temperature Range: 10 to 32.5° C; Recommended Operating Temperature: 50 to 91° F (10 to 32.5° C); Maximum Operating Temperature: 50 to 91° F; Storage Temperature Range: 32 to 95° F (0 to 35° C); Non-Operating Humidity Range: 10 to 80% RH; Operating Humidity Range: 10 to 80% RH;
ENVIRONMENT	Operating Temperature Range: 10 to 32.5° C; Recommended Operating Temperature: 50 to 91° F (10 to 32.5° C); Maximum Operating Temperature: 50 to 91° F; Storage Temperature Range: 32 to 95° F (0 to 35° C); Non-Operating Humidity Range: 10 to 80% RH; Operating Humidity Range: 10 to 80% RH; Recommended Humidity Operating Range: 10 to 80% RH W X D X H: 17.1 x 10.4 x 12 in (435 x 265 x 306 mm);
PRODUCT DIMENSIONS	Operating Temperature Range: $10 \text{ to } 32.5^{\circ} \text{ C}$; Recommended Operating Temperature: $50 \text{ to } 91^{\circ} \text{ F}$ ($10 \text{ to } 32.5^{\circ} \text{ C}$); Maximum Operating Temperature: $50 \text{ to } 91^{\circ} \text{ F}$; Storage Temperature Range: $32 \text{ to } 95^{\circ} \text{ F}$ ($0 \text{ to } 35^{\circ} \text{ C}$); Non-Operating Humidity Range: $10 \text{ to } 80\% \text{ RH}$; Operating Humidity Range: $10 \text{ to } 80\% \text{ RH}$; Recommended Humidity Operating Range: $10 \text{ to } 80\% \text{ RH}$ W X D X H: $17.1 \times 10.4 \times 12 \text{ in } (435 \times 265 \times 306 \text{ mm})$; Maximum: $17.1 \times 14.4 \times 12 \text{ in }$
PRODUCT DIMENSIONS PRODUCT WEIGHT	Operating Temperature Range: 10 to 32.5° C; Recommended Operating Temperature: 50 to 91° F (10 to 32.5° C); Maximum Operating Temperature: 50 to 91° F; Storage Temperature Range: 32 to 95° F (0 to 35° C); Non-Operating Humidity Range: 10 to 80% RH; Operating Humidity Range: 10 to 80% RH; Recommended Humidity Operating Range: 10 to 80% RH W X D X H: 17.1 x 10.4 x 12 in (435 x 265 x 306 mm); Maximum: 17.1 x 14.4 x 12 in 18.3 lb (8.3 kg) HP LaserJet Pro M1212nf MFP, power cord(s), phone cord(s), 150-sheet input tray, output tray, introductory HP LaserJet Black print cartridge, Readiris PRO text recognition software, CD(s) with software and documentation, Installation Guide, support flyer, Errata sheet, Discovery Sheet, Ferrite with flyer, Warranty Guide (where
PRODUCT DIMENSIONS PRODUCT WEIGHT WHAT'S IN THE BOX	Operating Temperature Range: 10 to 32.5° C; Recommended Operating Temperature: 50 to 91° F (10 to 32.5° C); Maximum Operating Temperature: 50 to 91° F; Storage Temperature Range: 32 to 95° F (0 to 35° C); Non-Operating Humidity Range: 10 to 80% RH; Operating Humidity Range: 10 to 80% RH; Recommended Humidity Operating Range: 10 to 80% RH W X D X H: 17.1 x 10.4 x 12 in (435 x 265 x 306 mm); Maximum: 17.1 x 14.4 x 12 in 18.3 lb (8.3 kg) HP LaserJet Pro M1212nf MFP, power cord(s), phone cord(s), 150-sheet input tray, output tray, introductory HP LaserJet Black print cartridge, Readiris PRO text recognition software, CD(s) with software and documentation, Installation Guide, support flyer, Errata sheet, Discovery Sheet, Ferrite with flyer, Warranty Guide (where applicable)
PRODUCT DIMENSIONS PRODUCT WEIGHT WHAT'S IN THE BOX WARRANTY REPLACEMENT	Operating Temperature Range: 10 to 32.5° C; Recommended Operating Temperature: 50 to 91° F (10 to 32.5° C); Maximum Operating Temperature: 50 to 91° F, Storage Temperature Range: 32 to 95° F (0 to 35° C); Non-Operating Humidity Range: 10 to 80% RH; Operating Humidity Range: 10 to 80% RH; Recommended Humidity Operating Range: 10 to 80% RH W X D X H: 17.1 x 10.4 x 12 in (435 x 265 x 306 mm); Maximum: 17.1 x 14.4 x 12 in 18.3 lb (8.3 kg) HP LaserJet Pro M1212nf MFP, power cord(s), phone cord(s), 150-sheet input tray, output tray, introductory HP LaserJet Black print cartridge, Readiris PRO text recognition software, CD(s) with software and documentation, Installation Guide, support flyer, Errata sheet, Discovery Sheet, Ferrite with flyer, Warranty Guide (where applicable) One-year limited warranty HP LaserJet Black Print Cartridge, CE285A;

ADDITIONAL INFORMATION

BUSINESS UNIT	Transaction Laser Products
COUNTRY OF ORIGIN	Product of China; Brazil
MATERIAL TYPE CODE	FERT
PALLET INFORMATION	Dimensions: 47.24 x 39.37 x 96.73 in Weight: 881.5 lb Layers: 7

FOR MORE INFORMATION VISIT OUR WEBSITE AT WWW.HP.COM

HP LASERJET PRO M1212NF MULTIFUNCTION PRINTER Product Number: CE841A

Exact speed varies depending on the system configuration, software program, and document complexity. ²Acoustic values are subject to change. For current information, see http://www.hp.com/support. Configuration tested: LaserJet Pro M1212nf MFP printing simplex on A4 paper