



Hyper 212 LED Turbo (Red Top Cover)



Hyper 212 LED Turbo (Red Top Cover) is equipped with red top cover and dual PWM fans with red LEDs, providing the best balance between airflow and static pressure to take the heat away. Four Direct Contact heat pipes with funnel shaped aluminum fins optimize cooling for optimal CPU performance. Moreover, the improved universal bracket design ensures easy and worry free installation on all platforms.

Product Features

- Four Direct Contact heat pipes between CPU and cooler.
- Premium aluminum top cover.
- Dual 120mm fans with quick snap fan bracket.
- Wide-range PWM fan with unique blade design and red LEDs.
- Versatile all-in-one mounting solution for Intel and AMD sockets.
- Optimized bracket design for easy installation.

Package Information

EAN Code	4719512054147
UPC Code	884102030246
Carton Dimensions	658 x 325 x 240 mm (25.9 x 12.8 x 9.45")
Unit / Carton	10 pcs
Carton / Pallet	32
Gross Weight	11.537 kg

Specification

	Intel® LGA
	2011-v3/ 2011/ 1366/ 1151/ 1150/ 1155/ 1156/
CPU	775 socket
	AMD
	AM4/ AM3+/ AM3/ AM2+/ FM2+/ FM2/ FM1 socket
Dimensions	120 x 108 x 163 mm (4.7 x 4.3 x 6.4")
	Dimensions 120 x 60 x 160 mm (4.7 x 2.4 x 6.3")
Heat Sink	Material Aluminum Fins (4 Heat Pipes / Direct Contact)
	Weight 468 g
	Heat Pipe Ø6 mm
	Dimensions
	Dimensions 120 x 120 x 25 mm (4.7 x 4.7 x 1")
	Speed 600 ~ 1600 RPM (PWM) ± 10%
Fan	Air Flow 66.3 CFM ± 10%
	Air Pressure 1.7 mm H ₂ O ± 10%
	MTTF 40,000 hours
Noise Level	9 ~ 31 dBA
Connector	4-Pin
Rated Voltage	12 VDC
Rated Current	0.19 A
Power Consumption	2.28 W
Warranty	2 Years