



M200 Portable SSD

83g. It can up to 2000MB/s in transmission speeds and offers up to 8TB of storage that can easily house all your 4K UHD videos. Uses patented graphene cooling technology from TEAMGROUP to wrap up the dual metallic structure for ultimate cooling and stable transmissions. Enjoy lightning fast transmission speeds with T-FORCE M200. The unique tactical, military-style hanging hole on the T-FORCE M200 delivers maximum portability and convenience.

LICES 2 Con 2v2 Type C[3]

Main Feature

- Tactical, military-style hanging hole. Ultra-light and portable
- Lightning fast speeds of USB 3.2 Gen2x2 20Gbps transmissions
- Massive 8TB storage for any large audio or video files
- Designs inspired by the M200 sniper rifle
- Dual structure for ultimate cooling
- 2-Meter drop resistant^[4]
- Wide compatibility with gaming consoles

Specification Interface

Interrace	USB3.2 Gen2x2 Type-C ¹³	
Capacity	250GB / 500GB / 1TB / 2TB / 4TB / 8TB ^[2]	
Color	Black	
Operation Temperature	0°C to 70°C	
Storage Temperature	-40°C ~ 80°C	
Weight	83g	
Dimensions	105(L) x 55.5 (W) x 11 (H) mm	
Operating System	Works with Windows® 11, Windows® 10, Windows® 8.1, mac OS®	
	x 10.11 or higher, Linux© 2.6. or higher, PlayStation™ 4 with	
	system software version 4.50 or higher, PlayStation™ 5 (play and	
	store PS4 games or archive PS5 Games),Chrome OS®*	
	*All registered trademarks belong to their respective companies.	
Transmission rate	250GB Read/Write: up to 1900/1500 MB/s	
	500GB/1TB/2TB/4TB/8TB Read/Write: up to 2000/2000 MB/s ^[1]	
Accessories	USB 3.2 Type-C - C Cable (20Gbps)*1 ^[5]	
Warranty	5-year limited warranty	



Ordering Information

Capacity	Team P/N
250GB	T8FED9250G0C102
500GB	T8FED9500G0C102
1TB	T8FED9001T0C102

Capacity	Team P/N
2TB	T8FED9002T0C102
4TB	T8FED9004T0C102
8TB	T8FED9008T0C102

- [1] The transmission speed of 2000 MB/s is obtained through the Crystal Disk Mark 8.0.1 software (SEQ1M Q32T1 0x00)
- but transmission speeds will vary based on hardware and software. Best wink 60.1 software (Septimose)

 [2] Part of the capacity of FLASH storage products will be used for formatting or other functions, and the displayed capacity in the operating system will be less than the actual storage capacity
 due to unit conversion. It is recommended to calculate the actual storage capacity based on this equation: total bytes/1024/1024/1024/1024.

 [3] When using an external storage device, please confirm connection via the correct port to ensure operating performance. For example, the USB3.2 Gen2x2 interface of a storage product should be connected via the
 corresponding port of USB 3.2 Gen2 interface. If the port is of an older-version interface, transmission will be limited by the older-version interface, which leads to the reduction of transmission speed.

 [4] Up to 2 meter without impact on data on drive on a carpeted floor. However, it is not guaranteed that the SSD, appearance, and data will not be damaged in all environments. Do not drop or damage the product
- [5] To ensure regular and stable function under the labeled reading and writing speeds on compatible mobile devices, laptops and PCs, please use the transmission cable included in the package when connecting
- *All the test data is provided by TEAMGROUP's laboratory and the information of test data is only for reference. We reserve the right to modify product specifications without prior notice







