



TS-431K CPU AnnapurnaLabs, an Amazon company Alpine AL214, 4-core, 1.7GHz CPU Architecture 32-bit ARM Wake on LAN (WOL) Yes Floating Point Unit Yes Encryption Engine Yes System Memory 1GB DDR3 Maximum Memory 1GB DDR3 Flash Memory 512 MB (Dual boot OS protection) Drive Bay 4x 3.5-inch SATA 6Gb/s, 3Gb/s Drive Compatibility 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
CPU Architecture 32-bit ARM Wake on LAN (WOL) Yes Floating Point Unit Yes Encryption Engine Yes System Memory 1GB DDR3 Maximum Memory 1GB DDR3 Flash Memory 512 MB (Dual boot OS protection) Drive Bay 4x 3.5-inch SATA 6Gb/s, 3Gb/s Drive Compatibility 3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Wake on LAN (WOL) Floating Point Unit Yes Encryption Engine Yes System Memory 1GB DDR3 Maximum Memory 1GB DDR3 Flash Memory 512 MB (Dual boot OS protection) Drive Bay 4x 3.5-inch SATA 6Gb/s, 3Gb/s Drive Compatibility 3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Floating Point Unit Yes Encryption Engine Yes System Memory 1GB DDR3 Maximum Memory 1GB DDR3 Flash Memory 512 MB (Dual boot OS protection) Drive Bay 4x 3.5-inch SATA 6Gb/s, 3Gb/s Drive Compatibility 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Encryption Engine Yes System Memory 1GB DDR3 Maximum Memory 1GB DDR3 Flash Memory 512 MB (Dual boot OS protection) Drive Bay 4x 3.5-inch SATA 6Gb/s, 3Gb/s Drive Compatibility 3.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
System Memory 1GB DDR3 Maximum Memory 1GB DDR3 Flash Memory 512 MB (Dual boot OS protection) Drive Bay 4x 3.5-inch SATA 6Gb/s, 3Gb/s Drive Compatibility 3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Maximum Memory 1GB DDR3 Flash Memory 512 MB (Dual boot OS protection) Drive Bay 4x 3.5-inch SATA 6Gb/s, 3Gb/s Drive Compatibility 3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Flash Memory 512 MB (Dual boot OS protection) Drive Bay 4x 3.5-inch SATA 6Gb/s, 3Gb/s Drive Compatibility 3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Drive Bay 4x 3.5-inch SATA 6Gb/s, 3Gb/s Drive Compatibility 3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Drive Compatibility 3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
3.5-inch SATA hard disk drives 2.5-inch SATA solid state drives 2.5-inch SATA solid state drives
Hot-swappable Yes
SSD Cache Acceleration Yes Support
Gigabit Ethernet Port 2 (RJ45)
Jumbo Frame Yes
USB 3.2 Gen 1 port 3
Form Factor Tower
LED Indicators Power, Status, LAN, USB, HDD1-4
Buttons Power, Reset, USB Auto Copy
Dimensions (HxWxD) $169 \times 160 \times 219 \text{ mm}$
Weight (Net) 2.01 kg

Weight (Gross)	3.47 kg
Operating temperature	0 - 40 °C (32°F - 104°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	90W Adapter, 100-240V
Power Consumption: HDD Sleep Mode	11.928 W
Power Consumption: Operating Mode, Typical	26.57 W
Fan	1 x 120mm, 12VDC
Sound Level	21.3 db(A)
System Warning	Buzzer
Kensington Security Slot	Yes
Max. Number of Concurrent Connections (CIFS)	400

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

Designs and specifications are subject to change without notice.

^{*} Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.