

iFace950

Multi-Biometric T&A and Access Control Terminal



ZKTeco has released the iFace950 Multi-Biometric T&A and Access Control Terminal which supports 3,000 face templates, 2,000 fingerprint templates and 10,000 cards (optional). It is equipped with ZKTeco latest hardware platform and algorithm, which provide clients with a brand new UI and user-friendly operating interface, bringing them a smooth using experience. With the advanced face algorithm and multi-biometric verification technology, the terminal's security level of verification is greatly enhanced.

Features

- 3,000 face and 2,000 fingerprint templates
- Multi-languages
- High verification speed
- Advanced and user-friendly UI
- Chip encryption for firmware protection
- Optional built-in battery backup providing approximately 4 hours of continuous operation

- Easy to extend functions and customize client's requirements
- One face template is registered for one user only
- Able to detect whether the face is an actual face or a photo, enhancing the security level of verification

Specifications

| Display | 4.3-Inch Touch Screen |
|-----------------------|--|
| Face capacity | 3, 000 (1:N) |
| Fingerprint capacity | 2, 000 |
| ID Card capacity | 10,000 (optional) |
| Logs capacity | 100, 000 |
| Communication | TCP/IP, RS232/485, USB Host |
| Standard Functions | Automatic Status Switch, Self-Service Query, Work Code, SMS, |
| | DST, T9 Input, 9 Digit User ID, Scheduled Bell, Photo ID, ADMS |
| Interfaces for | 3rd Party Electric Lock, Door Sensor, Exit Button, Alarm |
| Wiegand Signal | Output |
| Optional Functions | ID/Mifare/HID, 2000 mAh Backup Battery, Wi-Fi, 3G |
| Power Supply | 12V 3A |
| Operating Temperature | 0 °C- 45 °C |
| Operating Humidity | 20%-80% |
| Dimensions | 194.1*169*109.0mm (Length*Width*Thickness) |
| Package Weight | 1.6 kg |

Configuration

What's in the Box



